

#### MAIN FLOOR FRAMING

- SUPPORT POSTS AND BRACKETS FOR UNDER FLOOR BEAMS.
- ALL FLOOR BEAMS # METAL JOIST HANGERS.
- 3 SILL SEAL.
- 4 TREATED SILL PLATE.
- (5) 2X I O FLOOR JOISTS.
- 6 2X I O DOUBLE RIM JOISTS.
- 7 SOLID FLOOR JOIST BLOCKING.
- 8 3/4" OSB WAFER BOARD SUB-FLOOR DECKING.
- 9 SUB-FLOOR CONSTRUCTION ADHESIVE.
- SIMPSON A35 ANGLES.
- IX12 ROUGH SAWN BELLY BAND.

#### DECK FRAMING

- SUPPORT POSTS AND BRACKETS FOR UNDER DECK SUPPORT.
- 3 2X8 DECK JOISTS & SIMPSON METAL JOIST HANGERS.
- 2X10 DOUBLE OUTSIDE DECK GIRDER.
- (5) 2XG REDWOOD DECKING.

## INTERIOR WALL FRAMING

ALL INTERIOR FRAMING -- STUDS PLATES, HEADERS, BLOCKING.

# EXTERIOR WALLS & GABLES

- SWEDISH COPE WALL LOGS WITH SADDLE NOTCH CORNERS.
- (8) FULL LOG GABLES OR STICK FRAMED WITH BATT & BOARD SIDING OR HALF LOG SIDING.

#### ITEMS FOR LOG CONSTRUCTION

- O CONSTRUCTION ADHESIVE APPLIED TO EACH COURSE AS IT IS STACKED.
- SASHCO LOG CAULKING. AROUND DOORS, WINDOWS AND CORNERS
- (21) WOOD DOWELS FOR BUTT JOINTS.
- (22) BLUE OX LOG SCREWS @ 32" O.C. MAX.
- (23) 3" WIDE WINDOW AND DOOR BUCKING.

#### UPPER FLOOR FRAMING

- 24) 2X I O LEDGER BOARDS & LAG BOLTS.
- (25) 2X I O FLOOR JOISTS & BLOCKING.
- (26) SIMPSON METAL JOIST HANGERS.
- 3/4" OSB WAFER BOARD SUB-FLOOR DECKING.
- SUB-FLOOR CONSTRUCTION ADHESIVE.
- 1X6 T&G KNOTTY PINE FOR THE CEILING BELOW.

## STAIR FRAMING

2X12 STRINGERS, 1-1/4" X 12" TREADS. 7/16" OSB RISERS, ALL LANDING FRAMING.

#### VINYL WINDOWS

(31) VINYL FRAME, DUEL PANE, LOW-E.

#### EXTERIOR DOORS

METAL, 6 PANEL FRONT DOOR. VINYL SLIDERS, AND PATIOS.

## ROOF FRAMING

- (33) ENGINEERED GLULAM RIDGE BEAM.
- 34 2X | 2 ROOF RAFTERS.
- 35 2X | 2 FREEZE BLOCKING.
- 36 SIMPSON METAL RAFTER HANGERS.
- 2X6 SUB FASCIA WITH 1X8 ROUGH SAWN FINISH FASCIA.
- (38) 5/8" OSB WAFER BOARD SHEATHING.
- 39 5/8" CDX PLYWOOD OVER OPEN SOFFITS.
- 40 2X6 OUTRIGGERS.
- (4) IX6 T&G KNOTTY PINE FOR ALL CEILINGS.
- 42 ROOFING UNDERLAYMENT.
- 43 30 YR. ARCH. SHINGLES. METAL ROOF WITH MATCHING TRIM IS AN OPTION.
- 44 FULL LOG CENTER SUPPORT COLUMN.

## PORCH ROOF FRAMING

- FULL ROUND LOG SUPPORT COLUMNS AND GIRDERS.
- 46 2X8 PORCH RAFTERS.
- 47 2X8 BLOCKING ON TOP OF LOG GIRDER.
- 48 5/8" OSB WAFER BOARD SHEATHING.
- 49 5/8" CDX PLYWOOD OVER OPEN SOFFITS.
- (50) IXG T#G KNOTTY PINE FOR PORCH CEILING.

#### EXTERIOR LOG PROTECTION

(51) EXTERIOR LOG STAIN. TWO COATS.